



- NOTES**
1. ALL DIMENSIONS ARE IN MILLIMETERS AND LEVELS ARE IN METERS.
 2. UNLESS SPECIFIED OTHERWISE
 3. DIMENSIONS SHALL NOT BE SCALED FROM THE DRAWING ONLY
 4. WRITTEN DIMENSIONS TO BE FOLLOWED. DIMENSIONS OF RC CLASS
 5. A OR 11 LANE OF 200 WHICH EVER IS CRITICAL FOR EACH OF
 6. THE TWO STRUCTURAL UNITS IN OVERALL WIDTH
 7. WEIR HOLES AT 2000mm C/C HORIZONTALLY AND 1000 mm
 8. ABOVE BED LEVEL
 9. FILTER MEDIA 600mm WIDTH SHALL BE PROVIDED BEHIND BOX.
 10. TYPE ABUTMENT
 11. CLEAR COVER TO THE OUTER MOST REINFORCEMENT SHALL
 12. BE AS PER CODAL PROVISIONS.
 13. AT ONE SECTION NOT MORE THAN 20% OF BARS SHALL BE LAPPED
 14. ON SIDE OF CARRIAGEWAY & WATER SPOUT SHALL BE PROVIDED AT 3M C/C
 15. ALL EXPANSION JOINTS SHALL BE OF STRIP SEAL TYPE.
 16. DESIGN VELOCITY SHALL BE CONFIRMED BY BIDDER.