Pimpri Chinchwad Municipal Corporation

Name of the Work: Providing, laying and Fixing Natural Flair Paver Block of size 247.50 x 165 x 60mm (Grey and Brown Colour).

Rate analysis

Date :- 7/8/2018

Item: Providing & laying Natural Flair Shot blasted paver block of 60mm thick non-slippery concrete paving blocks of size 247.50 x 165.00 x 60mm thickness, the paver block should be of bevelled edges with face of block giving undulating guide, in grey and brown colour as per the IS 15658-2006, laying paving blocks in position over prepared bed of natural sand / crushed sand of 50 mm. The block should have exposed aggregate be shot blasted and bossed surface material made of high quality aggregate with colour UV stabilized and made from rich oxides. Block to be manufactured in fully automatic ISO certified vibration compaction machine having strength of M40 & cured in controlled temperature through mist. Transportation and fixing on site with all material and labour, including transportation, loading, unloading and all other taxes and excluding GST.

Lowest rate from comparative, hence rate proposed is

Rs.750 (Rs Seven Hundred and Fifty Only) Per Sq.m. for size 247.5x165x60mm (Grey Colour).

Rs. 800 (Rs. Eight Hundred Only) Per Sq.m. for size 247.5x165x60mm (Brown Colour).

Jr. Engineer (BRTS)	Dy. Engineer (BRTS)	Executive. Engineer (BRTS)
PCMC, Pimpri-18	PCMC, Pimpri-18	PCMC, Pimpri-18

Rate is Approved as

Rs. 750/- (Rs Seven Hundred and Fifty Only) Per Sq.m.for size 247.5x165x60mm (Grey Colour).

Rs. 800 (Rs. Eight Hundred Only) Per Sq.m. for size 247.5x165x60mm (Brown Colour).

DE

Jt. City Engineer (BRTS)

PCMC, Pimpri-18

Pimpri Chinchwad Municipal Corporation

Name of the Work: Providing, laying and Fixing Natural Flair Paver Blockof Size 165x165x60mm (Black and Terracotta Colour).

Rate Analysis

Item: Providing & laying Natural Flair Shot blasted paver block of 60mm thick non-slippery concrete paving blocks of size 165 x 165.00 x 60mm thickness, the paver block should be of bevelled edges with face of block giving undulating guide, in Black and Terracotta colour as per the IS 15658-2006,laying paving blocks in position over prepared bed of natural sand / crushed sand of 50 mm. The block should have exposed aggregate be shot blasted and bossed surface material made of high quality aggregatewith colour UV stabilized and made from rich oxides. Block to be manufactured in fully automatic ISO certified vibration compaction machine having strength of M40 & cured in controlled temperature through mist. Transportation and fixing on site with all material and labour, including transportation, loading,unloading and all other taxes and excluding GST.

Lowest rate from comparative, hence rate proposed is Rs.800 (Rs. Eight Hundred Only)Per Sq.m for Size 165x165x60mm (Black and Terracotta).

Jr. Engineer (BRTS)
PCMC, Pimpri-18

Dy. Engineer (BRTS)
PCMC, Pimpri-18

Executive. Engineer (BRTS)
PCMC, Pimpri-18

Rate is approved as Rs.800/- (Rs Eight Hundred) Per Sq.m for size165x165x60mm (Black and Terracotta Colour.

DE

Jt. City Engineer (BRTS)
PCMC, Pimpri-18

HasthShilp
sculpting structures

Red

Grey

Black

Sandstone

Brown

Terracotta

Orange

NATURAL FLAIR

The paving stone with the bossed and ball-blasted surfaces

The natural flair paving stone is characterized by its shot blasted and bossed surface material made of high quality aggregate. The beveled edges and undulating guide gives the stone its own unique character.

Textures:

Bossed

Dimensions:

165 x 124 x 60 mm

165 x 165 x 60 mm

247.5 x 165 x 60 mm

247.5 x 247.5 x 60 mm

247.5 x 330 x 60 mm